

# HELIO

## Outer Acrylic Interior Pendant



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.

**LED Dimming:** Standard 1% 0-10V integral dimming drivers. TRIAC, DALI, or DMX available upon request.


**Acrylic:** Satin white seamless outer acrylic is UL-94 HB Flame Class rated.




**Cable Hanger:** Comes with 72" cable and white cord for on-site adjustability.

**Canopy:** Painted textured white.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-2651-				B-	1-	A
MODEL NO.				LAMPING	HANGER	OPTIONS
<b>GL-2650</b>	W in 26" mm 660	20lbs B in 8 1/2" mm 215	9kg H in 20"-68" mm 510-1730	<b>M.</b> 4LED30 <b>F.</b> 4LED35 <b>N.</b> 4LED40	<b>1. Cable - Standard</b> 	<b>A. No Options</b> <b>LC.</b> 150" Cord & Cable Supplied with 150" Cord & Cable. <b>EL.</b> Emergency Ballast Integrally operates two LED strips. Integral test switch. Specify voltage after code.
<b>GL-2651</b>	W in 37 1/2" mm 950	30lbs B in 8 1/2" mm 215	13.5kg H in 20"-68" mm 510-1730	<b>C.</b> 6LED30 <b>B.</b> 6LED35 <b>E.</b> 6LED40	<b>2. Vertical Cable</b> 	
<b>GL-2652</b>	W in 52" mm 1320	40lbs B in 8 1/2" mm 215	18kg H in 20"-68" mm 510-1730	<b>I.</b> 10LED30 <b>J.</b> 10LED35 <b>R.</b> 10LED40	<b>3. Vertical Cable</b> 	

GL-2650 & GL-2651 (3) Canopies total.

GL-2652 (4) Canopies total.

All Dimensions are nominal.

### Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin	CRI
4LED30	52W	3837	3000	+90
4LED35	52W	3837	3500	+90
4LED40	52W	3837	4000	+90
6LED30	78W	6374	3000	+90
6LED35	78W	6374	3500	+90
6LED40	78W	6374	4000	+90
10LED30	131W	10840	3000	+90
10LED35	131W	10840	3500	+90
10LED40	131W	10840	4000	+90

Universal Voltage unless otherwise specified.  
Contact factory for availability of other lamp configurations.