

Evoked

Round Architectural Luminaire



Pendant
with Stem

Pendant
with Cable



Surface
Mount

Evoke

Pure Form. Balanced Light.

Defined by its smooth, circular profile and seamless silhouette, Evoke brings a refined presence to open spaces. Its soft geometry adds balance and visual clarity overhead, shaping the experience without overwhelming it.

Designed to integrate effortlessly into contemporary environments, Evoke delivers intentional illumination—creating a calm, cohesive atmosphere through light and form.

Construction
Extruded Aluminum Housing
Frosted Polycarbonate lens

Voltage
120-347V AC

UGR
18.7

Wattages
18: 30/40/50/60W
24: 140/60/80/100W
36: 60/100/140/175W

Beam Angle
120°

Dimming
0-10V

Selectable CCT
2700K, 3000K,
3500K, 4000K,
5000K

Life Hours
L70 > 50,000 hrs

Surge Protection
10kV

IRC
90

Mounting

Pendant Cable
Pendant Stem
Surface

Up to
22,942 lm | 3,096 lm Indirect)

Up to
125 lm/W

Dimensions
Ø18", 24", 36"
Height: 3.15"





Three Sizes One Seamless Form

Designed to adapt across a range of spaces



Finishes for Every Space

Standard white and black, custom finishes available



Direct
Distribution

Direct / Indirect
(80% / 20%)
Distribution

Shaping Light Defining Space

Direct and direct/indirect options, designed to shape the space



Prismatic Lens

Textured diffusion. Softer light.



UGR 18.7

Reduced glare. Enhanced comfort



Evoked pendant with stem with custom green finish



Evoked surface mount



2700K

3000K

3500K

4000K

5000K

Light, Tuned to the Environment

Selectable color temperature from warm to cool, shaping how a space is experienced



Evoke pendant

Reno Lighting



Evoke pendant



Evoke pendant with blue and red custom finishes



Evoke pendant with stem/pole



CA Office

#120- 9133 Leslie St., Richmond Hill, ON
L4B 4N1 Canada

US Office

#6728 - 735 Dunwoody Place, Atlanta, GA
30350 United States

info@renolighting.com

www.renolighting.com | arkbyreno.com